

# Switching Diode

## MMSD914, SMMSD914

### Features

- SOD-123 Surface Mount Package
- High Breakdown Voltage
- Fast Speed Switching Time
- S Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant\*

### MAXIMUM RATINGS

| Rating                                    | Symbol          | Value | Unit |
|-------------------------------------------|-----------------|-------|------|
| Continuous Reverse Voltage                | $V_R$           | 100   | Vdc  |
| Peak Forward Current                      | $I_F$           | 200   | mAdc |
| Peak Forward Surge Current                | $I_{FM(surge)}$ | 500   | mAdc |
| Non-repetitive Peak Forward Surge Current | $I_{FSM}$       |       |      |
| Pulse Width = 1 second                    |                 | 1.0   | A    |
| Pulse Width = 1 micro second              |                 | 2.0   | A    |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.


### THERMAL CHARACTERISTICS

| Characteristic                                                                                                 | Symbol          | Max         | Unit                      |
|----------------------------------------------------------------------------------------------------------------|-----------------|-------------|---------------------------|
| Total Device Dissipation FR-5 Board<br>(Note 1)<br>$T_A = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$ | $P_D$           | 425         | mW                        |
| Thermal Resistance,<br>Junction-to-Ambient                                                                     | $R_{\theta JA}$ | 3.4         | $^\circ\text{C}/\text{W}$ |
| Junction and Storage Temperature Range                                                                         | $T_J, T_{stg}$  | -55 to +150 | $^\circ\text{C}$          |

1. FR-5 = 1.0oz Cu, 1.0in<sup>2</sup> pad



SOD-123  
CASE 425  
PLASTIC



### MARKING DIAGRAM



5D = Specific Device Code  
M = Date Code  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

### ORDERING INFORMATION

| Device      | Package           | Shipping†            |
|-------------|-------------------|----------------------|
| MMSD914T1G  | SOD-123 (Pb-Free) | 3,000 / Tape & Reel  |
| SMMSD914T1G | SOD-123 (Pb-Free) | 3,000 / Tape & Reel  |
| MMSD914T3G  | SOD-123 (Pb-Free) | 10,000 / Tape & Reel |
| SMMSD914T3G | SOD-123 (Pb-Free) | 10,000 / Tape & Reel |


†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, [BRD8011/D](http://BRD8011/D).

\*For additional information on our Pb-Free strategy and soldering details, please download the [onsemi Soldering and Mounting Techniques Reference Manual, SOLDERRM/D](#).

# MMSD914, SMMSD914

## ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ unless otherwise noted)

| Characteristic                                                                              | Symbol     | Min    | Max       | Unit                    |
|---------------------------------------------------------------------------------------------|------------|--------|-----------|-------------------------|
| <b>OFF CHARACTERISTICS</b>                                                                  |            |        |           |                         |
| Reverse Breakdown Voltage ( $I_{BR} = 100 \mu\text{Adc}$ )                                  | $V_{(BR)}$ | 100    | –         | Vdc                     |
| Reverse Voltage Leakage Current<br>( $V_R = 20 \text{ Vdc}$ )<br>( $V_R = 75 \text{ Vdc}$ ) | $I_R$      | –<br>– | 25<br>5.0 | nAdc<br>$\mu\text{Adc}$ |
| Forward Voltage ( $I_F = 10 \text{ mAdc}$ )                                                 | $V_F$      | –      | 1000      | mVdc                    |
| Diode Capacitance ( $V_R = 0 \text{ Vdc}$ , $f = 1.0 \text{ MHz}$ )                         | $C_D$      | –      | 4.0       | pF                      |
| Reverse Recovery Time ( $I_F = I_R = 10 \text{ mAdc}$ ) (Figure 1)                          | $t_{rr}$   | –      | 4.0       | ns                      |



- Notes: 1. A  $2.0 \text{ k}\Omega$  variable resistor adjusted for a Forward Current ( $I_F$ ) of  $10 \text{ mA}$ .  
 2. Input pulse is adjusted so  $I_{R(\text{peak})}$  is equal to  $10 \text{ mA}$ .  
 3.  $t_p \gg t_{rr}$

**Figure 1. Recovery Time Equivalent Test Circuit**

# MMSD914, SMMSD914




Figure 2. Forward Voltage




Figure 3. Leakage Current





Figure 4. Capacitance


**SOD-123 2-LEAD, 1.60x2.69x1.16**  
**CASE 425**  
**ISSUE H**



DATE 29 FEB 2024



## NOTES:

1. DIMENSION AND TOLERANCING PER ASME Y14.5M, 2018
2. CONTROLLING DIMENSION: MILLIMETERS

| DIM | MILLIMETER |      |      |
|-----|------------|------|------|
|     | MIN.       | NOM. | MAX. |
| A   | 0.94       | 1.17 | 1.35 |
| A1  | 0.00       | 0.05 | 0.10 |
| A2  | 1.16 REF.  |      |      |
| b   | 0.51       | 0.61 | 0.71 |
| C   | —          | —    | 0.15 |
| D   | 1.40       | 1.60 | 1.80 |
| E   | 2.54       | 2.69 | 2.84 |
| H   | 3.56       | 3.68 | 3.86 |
| L   | 0.25 REF.  |      |      |
| ⌀   | 0°         |      | 10°  |
| θ1  | 0°         |      | 10°  |


**GENERIC**  
**MARKING DIAGRAM\***


XXX = Specific Device Code  
M = Date Code  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

STYLE 1:  
PIN 1. CATHODE  
2. ANODE

|                         |                                       |                                                                                                                                                                                  |
|-------------------------|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98ASB42927B</b>                    | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>SOD-123 2-LEAD, 1.60x2.69x1.16</b> | <b>PAGE 1 OF 1</b>                                                                                                                                                               |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at  
[www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)